
Product datasheet





FRONT PLATE 3-4 VIGI NSX/ **CVS250 VERTICAL FIXED** TOGGLE WIDTH 600/650 7M

03241

! Discontinued on: 7 Jul 2022

! Discontinued

Main

Range	Prisma
Range Of Product	Prisma G Prisma P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P cubicle
Type Of Front Plate	Cut-out
Installed Device	ComPact: fixed NSX100160 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS100160 with earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS250 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX100160 with earth leakage protection - control: toggle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: toggle - vertical installation
Poles Description	4 x 3P: mounting plate support: CVS100160 vertical installation 3 x 4P: mounting plate support: CVS100160 vertical installation 4 x 3P: mounting plate support: CVS250 vertical installation 3 x 4P: mounting plate support: CVS250 vertical installation 4 x 3P: mounting plate support: NSX100160 vertical installation 3 x 4P: mounting plate support: NSX100160 vertical installation 4 x 3P: mounting plate support: NSX250 vertical installation 3 x 4P: mounting plate support: NSX250 vertical installation
Operating Position	Vertical

Complementary

Enclosure/Cubicle Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
Connection Position	Direct connection Linergy FC
Number Of Vertical Modules [50 Mm]	7
Standards	IEC 61439-1 IEC 61439-2
Product Certifications	ASEFA
Material	Steel

Life Is On Schneider 20 Apr 2024

Surface Finish	Matt Smooth	
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder	
Colour	White (RAL 9001)	
Height	350 mm	
Width	500 mm	
Net Weight	1.1 kg	
Quantity Per Set	Set of 1	

Functional Unit

650 mm 400 mm Prisma P cubicle EasyPact CVS100...160 with fixed toggle vertical 3P 4 direct 11

650 mm 400 mm Prisma P cubicle EasyPact CVS100...160 with fixed toggle vertical 4P 3 direct 11

650 mm 400 mm Prisma P cubicle EasyPact CVS250 with fixed toggle vertical 3P 4 direct 11

650 mm 400 mm Prisma P cubicle EasyPact CVS250 with fixed toggle vertical 4P 3 direct 11

650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed toggle vertical 3P 4 Linergy FC 8
650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed toggle vertical

4P 3 Linergy FC 8
650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed toggle vertical

3P 4 direct 10
650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed toggle vertical

4P 3 direct 10

650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with plug-in toggle vertical 3P 4 direct 11

 $650\ mm\ 400\ mm$ Prisma P cubicle ComPact NSX100...160 with plug-in toggle vertical 4P 3 direct 11

650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with plug-in toggle vertical 3P 4 Linergy FC 9

 $650~\rm mm$ $400~\rm mm$ Prisma P cubicle ComPact NSX100...160 with plug-in toggle vertical 4P 3 Linergy FC 9

650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed toggle vertical 3P 4 Linergy FC 9

650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed toggle vertical 4P 3 Linergy FC 9

650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed toggle vertical 3P 4 direct 11

650~mm 400~mm Prisma P cubicle ComPact NSX250 with fixed toggle vertical 4P 3 direct 11

 $650~\mathrm{mm}$ 400 mm Prisma P cubicle ComPact NSX250 with plug-in toggle vertical 3P 4 direct 12

650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in toggle vertical 4P 3 direct 12

650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in toggle vertical 3P 4 Linergy FC 10

650 mm 400 mm Prisma P cubicle ComPact NSX250 with plug-in toggle vertical 4P 3 Linergy FC 10

 $600~\rm mm$ Prisma G floor-standing enclosure EasyPact CVS100...160 with fixed toggle vertical 3P 4 direct with long terminal shield 10

600~mm Prisma G wall-mounted enclosure EasyPact CVS100...160 with fixed toggle vertical 3P 4 direct with long terminal shield 10 $\,$

600 mm Prisma G floor-standing enclosure EasyPact CVS100...160 with fixed toggle vertical 4P 3 direct with long terminal shield 10

600~mm Prisma G wall-mounted enclosure EasyPact CVS100...160 with fixed toggle vertical 4P 3 direct with long terminal shield 10

600 mm Prisma G floor-standing enclosure EasyPact CVS250 with fixed toggle vertical 3P 4 direct with long terminal shield 13 600 mm Prisma G wall-mounted enclosure EasyPact CVS250 with fixed toggle

vertical 3P 4 direct with long terminal shield 13

 $600~\rm mm$ Prisma G floor-standing enclosure EasyPact CVS250 with fixed toggle vertical 4P 3 direct with long terminal shield 13

600 mm Prisma G wall-mounted enclosure EasyPact CVS250 with fixed toggle vertical 4P 3 direct with long terminal shield 13

600 mm Prisma G floor-standing enclosure ComPact NSX100...160 with fixed toggle vertical 3P 4 direct with long terminal shield 10

600 mm Prisma G wall-mounted enclosure ComPact NSX100...160 with fixed toggle vertical 3P 4 direct with long terminal shield 10 600 mm Prisma G floor-standing enclosure ComPact NSX100...160 with fixed toggle

vertical 4P 3 direct with long terminal shield 10

600~mm Prisma G wall-mounted enclosure ComPact NSX100...160 with fixed toggle vertical 4P 3 direct with long terminal shield 10

600 mm Prisma G floor-standing enclosure ComPact NSX250 with fixed toggle vertical 3P 4 direct with long terminal shield 13 600 mm Prisma G wall-mounted enclosure ComPact NSX250 with fixed toggle

vertical 3P 4 direct with long terminal shield 13

600~mm Prisma G floor-standing enclosure ComPact NSX250 with fixed toggle vertical 4P 3 direct with long terminal shield 13

600 mm Prisma G wall-mounted enclosure ComPact NSX250 with fixed toggle vertical 4P 3 direct with long terminal shield 13

Packing Units

Unit Type Of Package 1

PCE

Number Of Units In Package 1

1

Package 1 Height	2.000 cm
Package 1 Width	36.000 cm
Package 1 Length	51.000 cm
Package 1 Weight	1.140 kg
Unit Type Of Package 2	CAR
Number Of Units In Package 2	10
Package 2 Height	17.000 cm
Package 2 Width	36.500 cm
Package 2 Length	54.000 cm
Package 2 Weight	11.400 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	160
Package 3 Height	83.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	185.280 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
⊘	Rohs Exemption Information Yes
Ø	Halogen Free Plastic Parts Product

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile