



### Main

Range	Prisma
Range compatibility	Prisma P
IP degree of protection	IP30
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Type of front plate	Cut-out
Installed device	Easypact : fixed CVS100...160 without earth leakage protection - control: toggle - horizontal installation Easypact : fixed CVS250 without earth leakage protection - control: toggle - horizontal installation Easypact : fixed CVS100...160 with earth leakage protection - control: toggle - horizontal installation Easypact : fixed CVS250 with earth leakage protection - control: toggle - horizontal installation
Poles description	1 x 4P : mounting plate support : CVS100...160 horizontal installation 1 x 4P : mounting plate support : CVS250 horizontal installation
Operating position	Horizontal

### Complementary

Enclosure/Cubicle description	Cubicle - width 650 mm, depth 400 mm
Connection position	Direct connection
Type of front plate	Cut-out
Number of vertical modules [50 mm]	4
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA
Quantity per set	Set of 1
Height	200 mm
Width	500 mm
Product weight	0.84 kg
Material	Steel
Surface finish	Matt

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Smooth

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White RAL 9001

## Environment

IK degree of protection	IK07 conforming to EN/IEC 62262
-------------------------	---------------------------------

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0701 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------