# **Product datasheet**



## LINERGY FM 3P DIS.BLOCK 200A 24M 42HOLES



Discontinued on: 7 Jul 2022



#### Main

Range	Linergy	
Range Of Product	Linergy	
Product Or Component Type	Device feeder	
Product Name	Linergy FM	
Range Compatibility	Prisma Prisma G enclosure Prisma Prisma P enclosure Prisma Prisma PH enclosure	
Product Compatibility	Spacial enclosures	
Ip Degree Of Protection	IPxx B	

### Complementary

Mounting Support	Plain backplate DIN rail Slotted backplate
Installed Device	modular device
Poles Description	3P
[Ue] Rated Operational Voltage	690 V AC
[Ui] Rated Insulation Voltage	750 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[le] Rated Operational Current	200 A
[In] Rated Current	200 A at 40 °C
[lpk] Rated Peak Withstand Current	20 kA
I <sup>2</sup> T On Activation	6700000 A².s
Connections - Terminals	Supply: crimped lug50 mm² Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 12 x 410 mm² (flexible) Distribution: quick-connect terminal strips (phase) , 12 x 410 mm² (rigid) Distribution: quick-connect terminal strips (neutral) , 18 x 410 mm² (flexible) Distribution: quick-connect terminal strips (neutral) , 18 x 410 mm² (rigid)
9 Mm Pitches	48
Total Number Of 18 Mm Modules	24
Net Weight	1.32 kg
Colour	Anthracite grey (RAL 7016)

#### **Environment**



Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
Product Certifications	ASEFA

# **Packing Units**

r adming dimes	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.7 cm
Package 1 Width	7.6 cm
Package 1 Length	44.7 cm
Package 1 Weight	1.28 kg
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	6.7 cm
Package 2 Width	37.6 cm
Package 2 Length	44.7 cm
Package 2 Weight	6.41 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	120
Package 3 Height	97 cm
Package 3 Width	80 cm
Package 3 Length	60 cm
Package 3 Weight	158.4 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Reach Free Of Svhc
<b>⊘</b>	Toxic Heavy Metal Free
<b>⊘</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>Ø</b>	Halogen Free Product

#### **Certifications & Standards**

**Eu Rohs Directive** 

	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Compliant