

Product datasheet

Specifications



time delay control ATet - 24..240 V AC - 24...110 V DC

15419

⚠ Discontinued on: 8 Feb 2019

⚠ Discontinued

Main

Product Or Component Type	Time delay auxiliary
Device Short Name	ATet
Signal Contacts Composition	1 NO
[Uc] Control Circuit Voltage	24...110 V DC impulse 24...240 V AC 50/60 Hz maintained

Complementary

Type Of Setting	Time delay configuration
Time Delay Range	1...36000 s
Mounting Mode	Fixed, on the left of TL or CT
Mounting Support	DIN rail
9 Mm Pitches	2
Height	84 mm
Width	18 mm
Depth	69.5 mm
Net Weight	0.07 kg
Connections - Terminals	Tunnel type terminals 2 cable(s) 2.5 mm² flexible Tunnel type terminals 2 cable(s) 1.5 mm² rigid
Range Compatibility	Multi9 Multi9 CT

Environment

Ambient Air Temperature For Operation	-20...60 °C
---------------------------------------	-------------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8 cm
Package 1 Width	2.2 cm
Package 1 Length	9 cm
Package 1 Weight	0.085 kg

Contractual warranty

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Warranty

18 months