

Product datasheet

Specifications



Ulti - 250V twin gang 13A switched BS socket module, amber LED

UST25A00

⚠ Discontinued on: 18 Apr 2022

⚠ Discontinued

Main

Range	Ulti
Device Application	Power supply
Product Or Component Type	Socket module
Number Of Gangs	2 gangs
Rated Current	13 A at 250 V AC 50 Hz

Complementary

Load Type	Resistive
Number Of Cables	3 cable(s) 2.5 mm ² 1 cable(s) 2.5 mm ² 2 cable(s) 2.5 mm ² 1 cable(s) 4 mm ² 2 cable(s) 4 mm ²
Fixing Mode	By screws
Wiring Device Mounting	Flush Surface
Distance Between Centers	120.6 mm
Width	87 mm
Height	147 mm
Depth	17.7 mm
Surface Treatment	Untreated
Surface Finish	Matt
Connections - Terminals	Screw terminals

Environment

Ambient Air Temperature For Operation	-5...40 °C
Relative Humidity	0...95 %
Environmental Characteristic	No UV resistant
Operating Altitude	<= 2000 m
Standards	MS 589 SS 145 BS

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Under investigation
